Surface Emissions Monitoring 1st Quarter 2016 Report

Prepared By:



American Environmental Group

3600 Brecksville Road Richfield, Ohio 44286 (330) 659-5930



March 31, 2016

Advanced Disposal Zion Landfill Jim Lewis 701 Green Bay Road Zion, IL 60099

RE: Advanced Disposal Zion Landfill – 1st Quarter 2016 NSPS Surface Scan

Dear Mr. Lewis,

American Environmental Group (AEG) prepared the enclosed report documenting the results of the 1st Quarter 2016 NSPS surface scan at Advanced Disposal Zion Landfill. The initial monitoring event was performed on March 18, 2016. We noted no (0) exceedances of the 500 parts per million methane by volume (ppm) standard at the facility during the initial scan event.

In summary, the site met the NSPS standards for surface emissions for the 1st Quarter 2016 Surface Scan event, and no further action is required. Field monitoring forms are attached for your files.

Weather Conditions

Weather conditions recorded during the monitoring events were as follows:

March 18, 2016:

- Temperature approximately 36° Fahrenheit
- Relative humidity of 74 percent
- Barometric pressure of 30.09"Hg
- Wind North northeast at about 7 mph
- Overcast skies

In accordance with NSPS regulations, these monitoring events were performed during typical meteorological conditions.

The survey was conducted in accordance with the regulations set forth in the New Source Performance Standard (NSPS), 40 CFR 60.755 (c) and (d); (2) 40 CFR 60, 40 CFR 60.753(d) - Surface Scan Requirements, Appendix A – Method 21. A Photovac (MicroFID) was used to perform the emissions monitoring. During the event, attention was given to monitoring unusual cover conditions (stressed vegetation, cracks, seeps, etc.) and areas with unusual odors. The MicroFID was calibrated at the beginning of each day, prior to performing the monitoring, in accordance with Method 21 compliance requirements. Calibration logs were completed by the field technician performing the work, and are included in Attachment A. During the monitoring event, AEG observed that the ground surface appeared to be in good condition overall and there were no unusual odors noted. Results are presented in the attached forms.

Please call Dave Ovanek at (815) 671-0203 if you have any questions.

Sincerely,

Pam Nyiri

Pan Nijiri

Environmental Data Coordinator III American Environmental Group, Ltd.

On Behalf of Dave Ovanek Project Manager American Environmental Group, Ltd.

Attachments: Surface Emissions Monitoring Calibration Logs

Surface Emissions Monitoring Log

Surface Emissions Monitoring Topographic Map with Monitoring Route

Cc: Jim Hitzeroth, Republic Services, Inc – Electronic

Surface Emissions Monitoring Calibration Logs



CALIBRATION PRECISION TEST RECORD

Initial Event: March 18, 2016

LANDFILL NAME: _	Zion Landfill-AD	os	EVENT:	1st Qu	arter 2016 SEM
INSTRUMENT MAKE: _	Photovac	MODEL:	MicroFID	SERIAL #:	CZWR424
PERFORMED BY: _	Bert Krueger	TIME:	8:00	DATE: _	March 18, 2016
Calibration Gas Stan	dard: 500ppm CH4				
MEASUREMENT # 1:					
Meter Reading	g for Zero Air:		-	1.0	ppm (1)
Meter Reading	g for Calibration Gas:		-	503.0	ppm (2)
MEASUREMENT # 2:					
Meter Reading	g for Zero Air:			1.0	ppm (3)
Meter Reading	g for Calibration Gas:		-	501.0	ppm (4)
MEASUREMENT # 3:					
Meter Reading	g for Zero Air:		-	1.0	ppm (5)
Meter Reading	g for Calibration Gas:			503.0	ppm (6)
CALCULATE PRECIS Must be less than 10%	SION:				
<u> 500 - (2) + </u>	<u>500 - (4) + 500 - (6) </u> 3	Χ _	<u>1</u> 500	х _	100 1
	_	0.467%			

SEM Calibration Logs 1 of 3



INSTRUMENT RESPONSE TIME TEST RECORD

Initial Event: March 18, 2016

LANDFILL N	AME:	Zion Landfill-ADS		EVENT:	1st Quarter 2016 SEM	
INSTRUMENT M	AKE:	Photovac	MODEL:	MicroFID	SERIAL #:	CZWR424
PERFORME	D BY:	Bert Krueger	TIME:	8:10	DATE:	March 18, 2016
MEASUREMEN	T # 1:					
Stabiliz	ed Readi	ng Using Calibrati	on Gas:		504.0	ppm
90% of	the Stabi	lized Reading:			453.6	ppm
		0% of Stabilized re Calibration Gas:	eading after sv	vitching	5.0	seconds (1)
MEASUREMEN	T # 2:					
Stabiliz	Stabilized Reading Using Calibration Gas: 501.0 ppm			ppm		
90% of	90% of the Stabilized Reading:				450.9	ppm
	Time to Reach 90% of Stabilized reading after switching from Zero Air to Calibration Gas: 6.0 seconds (2)					
MEASUREMEN	T # 3:					
Stabiliz	ed Readi	ng Using Calibrati	on Gas:		505.0	ppm
90% of	the Stabi	lized Reading:			454.5	ppm
		0% of Stabilized re Calibration Gas:	eading after sv	vitching	6.0	seconds (3)
CALCULATE R Must be less than			<u>(1) + (2) + (3)</u>	=	5.667	seconds
			3	· ·		

SEM Calibration Logs 2 of 3



CALIBRATION PROCEDURE & BACKGROUND DETERMINATION REPORT

Initial Event: March 18, 2016

LANDFILL NAME:	Zion Landfill-ADS		EVENT:	1st Quarter 2016 SEM			
INSTRUMENT MAKE:	Photovac	MODEL:	MicroFID	SERIAL #:	CZWR424		
PERFORMED BY:	Bert Krueger	TIME:	1016 am	DATE:	March 18, 2016		
CALIBRATION PROCEDURE							
1. Allow inst	rument to internally zero	o itself while	e introducino	g zero air.			
2. Introduce the calibration gas into the probe. Stable Reading = 501.0							
3. Adjust meter to read 500 ppm.							
BACKGROUND DETERMINATION PROCEDURE							
1. Upwind R	eading (highest in 30 se	econds):					
Location:	GMP16			1.9	ppm (1)		
	d Reading (highest in 30 GMP05) seconds):	-	1.3	ppm (2)		
CALCULATE BACK	GROUND VALUE	<u>(1) + (2)</u>	= .	1.6	ppm		

SEM Calibration Logs 3 of 3

Surface Emissions Monitoring Logs

Individual Monitoring Exceedance Surface Monitoring Design Plan

Use this form to record an individual monitoring exceedance and follow-up monitoring activities.

This form is only used when a reading of 500 ppm above background is encountered during the surface monitoring. *Use a separate form for each initial exceedance.*

Initial Monitoring Exceedance: #1		No Exceedances
Date: Time:	am/pm	Monitoring Technician Initials:
Instrument reading - Background reading:	ppm	ppm =ppm
Location of monitored exceedance (include descrip	ption of field mar	ker used):
Describe cover maintenance or adjustments to the measured exceedance before remonitoring in 10 da		ent wells to increase gas collection in vicinity of
Remonitor location within 10 calendar days of i	nitial exceedanc	ee:
Date: Time:	am/pm	Monitoring Technician Initials:
Instrument reading - Background reading:	ppm	ppm =ppm
If 10 day remonitoring shows an exceedance, describing the second state of the second		
If the 10 day remonitoring is <500 ppm, remonitor	1 month from i	nitial exceedance:
Date: Time:	am/pm	Monitoring Technician Initials:
Instrument reading - Background reading:	ppm	ppm =ppm
If the 1 month remonitoring is <500 ppm, resume r If the 1 month remonitoring shows an exceedance, again within 10 days:	describe addition	nal corrective action taken before remonitoring
again within 10 days.		
Remonitor location within 10 calendar days of 2	2nd exceedance:	
Date: Time:	am/pm	Monitoring Technician Initials:
Instrument reading - Background reading:	ppm -	ppm = ppm
If the 10 day remonitoring is <500 ppm, remonitor	1 month from in	itial exceedance:
Date: Time:	am/pm	Monitoring Technician Initials:
Instrument reading - Background reading:	ppm	ppm =ppm
If the 1 month remonitoring is <500 ppm, resume r If the 1 month remonitoring shows an exceedance, again within 10 days:		
(use additional forms if necessary)*		

*If monitoring shows 3 exceedances within a quarterly period a new well or other collection device must be installed within 120 days of initial exceedance or alternative remedies/timelines may be submitted to the Administrator for approval. Further monitoring is not necessary until the remedy is completed. The 3 exceedances do **not** have to be consecutive.

Surface Emissions Monitoring
Topographic map with monitoring route

Zion-Advanced Dispusal SEM 3-18-2016 O Exceedinces

